

Wear parts

ABIMIG® W 340


ABIMIG® W 440

ABIMIG® W 540



Gas nozzle incl. spatter protection ¹ (5 pcs.)	Ø A		Ø B		Ø C	
Cylindrical	Ø 17	145.0740.5	Ø 18	145.0745.5	Ø 20	145.0742.5
Conical	Ø 12.5	145.0737.5*	Ø 14.5	145.D092.5**	Ø 16	145.0735.5***
Conical	Ø 10	145.0739.5	Ø 12	145.0746.5	Ø 14	145.0741.5

The integrated spatter protection is already contained in the mentioned gas nozzles and can be ordered separately on request.



Contact tip (10 pcs.)		M6	M8	M8
E-Cu	Ø 0.8	140.0051	140.0114	-
	Ø 1.0	140.0242	140.0313	140.0313
	Ø 1.2	140.0379	140.0442	140.0442
	Ø 1.6	-	140.0587	140.0587
CuCr	Ø 0.8	140.0054	140.0117	-
	Ø 1.0	140.0245*	140.0316	140.0316
	Ø 1.2	140.0382	140.0445**	140.0445***
	Ø 1.6	-	140.0590	140.0590

For more contact tips see chapter "Accessories & special equipment"



Contact tip holder (5 pcs.)	X		X		X	
Brass	24.0	142.0241.5	26.0	142.0252.5	25.0	142.0239.5
	26.0	142.0242.5*	28.0	142.0253.5**	27.0	142.0240.5
	-	-	31.0	142.0243.5	28.5	142.0284.5***
CuCrZr	26.0	142.0274.5	29.5	142.0262.5	25.0	142.0247.5
	-	-	-	-	27.0	142.0248.5
	-	-	-	-	28.5	142.0261.5



Liner	Ø	for 3 m	for 4 m	for 5 m
Insulated liner	Ø 0.8	124.0137	124.0138	124.0139
	Ø 1.0	124.0111*	124.0112*	124.0113*
	Ø 1.2	124.0111***	124.0112***	124.0113***
	Ø 1.6	124.0114	124.0115	124.0116

For more liner see chapter "Accessories & special equipment"

Standard equipment

* Included in the standard equipment for complete torches ABIMIG® W 340

** Included in the standard equipment for complete torches ABIMIG® W 440

*** Included in the standard equipment for complete torches ABIMIG® W 540